

**L130 Access Terminal Specifications**

HARDWARE	
<b>Size</b>	Width: 115 mm / 4.5 inches, Depth: 115 mm / 4.5 inches, Height: 26 mm / 1 inches
<b>Weight</b>	L130 Access Terminal: 154 g / 0.34 lbs Shipping Weight (includes power adapter, packaging, documentation, etc.): 0.77 kg / 1.7 lbs
<b>Power Supply</b>	Input: 100-250 VAC, 50-60 Hz Output: 5 VDC, 2 A Nominal consumption: 5 Watts
<b>Front LED Indicators</b>	Power: connection to power supply LAN: connection to network Ready: connection to host PC
<b>Rear Ports</b>	<p>01 – Speaker Output 02 – Keyboard Port 03 – Mouse Port</p> <p>04 – LAN port (RJ45) 05 – Video port 06 – DC Power Input 07 – On/Off Power Switch</p>
<b>Connection to Host PC</b>	Via 100 Mb/s switched Ethernet connection
<b>Video Resolution**</b>	640x480, 800x600, 1024x768 (at 60 or 75 Hz refresh rate), 1280x1024 (~63 Hz) and 1440x900 (60Hz). All feature up to 16-bit color support.
<b>Audio</b>	Stereo output via speaker port
<b>Data Security</b>	No USB ports on terminal ensure absolute data security
<b>Internal HW</b>	All solid-state design, no moving parts, no fans, no local user storage NComputing System-on-Chip with SDRAM and flash Embedded NComputing operating firmware (no local user OS)
<b>Reliability (MTBF)</b>	>>100,000 hours (calculated using Bellcore Issue 6 TR-332, Case 2, Part I at 40°C)
<b>HW Security</b>	No local user storage
<b>Certifications</b>	FCC Class B, CE, MIC, NOM, GOST R and RoHS compliant (China RoHS (50))
TERMINAL SERVICES SOFTWARE	
<b>Max # Users Per PC</b>	30 users* when using a server host OS (i.e. Windows Server 2003) 10 users when using a desktop OS (i.e. Windows XP)
<b>User Software</b>	NAccess terminal services software with User eXtension Protocol (UXP)
<b>Supported Operating Systems</b>	Microsoft: Windows XP Professional and Media Center Edition 2005 Windows Server 2003, Small Business Server 2003 Linux: several variants (refer to support section of Website for latest supported revisions of Linux)
<b>Maintenance</b>	Online remote update via NAccess Management Console (included)
SYSTEM REQUIREMENTS AND OPTIONS	
<b>Host PC Configuration</b>	See Recommended Host Configuration Guide at: <a href="http://www.ncomputing.com/ncomputing/support/download.php">http://www.ncomputing.com/ncomputing/support/download.php</a>
<b>Kit Contents</b>	L130 Kit includes access terminal, power supply/cord, software installation & user's guide CD/license, Quick Install Guide, monitor mounting bracket and LAN cable. PC, monitor, PS/2 keyboard, PS/2 mouse, speakers and other peripherals are NOT included and must be purchased separately.
<b>Optional Software</b>	NControl (remote control and management), NShield (hard drive partition recovery)

\*The number of users an individual host will support depends upon the host system capabilities as well as the applications used and performance expectations for those applications. It is recommended that new customers test their application(s) before adding additional users.

\*\*Does not support 3D games or full screen home theater video applications.

\*\*\*Application software and OS licenses for the host PC and L200 may be required by the respective software vendor and must be purchased separately.

© Copyright 2007. NComputing Inc. All rights reserved. Specifications are subject to change without notice. NComputing is a trademark of NComputing Inc. Microsoft and Windows are registered trademarks of Microsoft Corporation. Linux is a registered trademark of Linus Torvalds. Other trademarks and trade names are the property of their respective owners.

10.3.07