


X300 Access Terminal Kit Specifications

HARDWARE	
Size	Access Terminal: <i>Width:</i> 110 mm / 4.3 inches, <i>Height:</i> 28 mm / 1.1 inches, <i>Depth:</i> 65 mm / 2.6 inches PCI Card: Low profile PCI plug-in card (includes standard and low profile PCI bracket)
Power Supply	No external power adapters are required Power to the access terminals is provided by the PCI card through the cable
LED Indicator	<i>Power/Connection:</i> Green LED located on front of access terminal
Peripheral Connections	 <p style="margin-left: 200px;">Connections (left to right):</p> <ul style="list-style-type: none"> - Speaker Jack - PS/2 Keyboard Port* - PS/2 Mouse Port* - VGA Monitor Port - RJ-45 Connection (to PC via Cat 5/6 cable)
Connection to Host PC	Standard Category 5 or 5e UTP cable: up to 5 meters (16 feet) Standard Category 6 STP cable: up to 7 meters (23 feet)
Video Resolution	800x600 and 1024x768, 16-bit color maximum, 60 Hz refresh rate
Audio	Stereo output via speaker port
Data Security	No USB ports on terminal ensure absolute data security USB ports on host PC can be assigned to different users <i>Note:</i> Local user access to USB ports requires separate USB extension cables – not included
Reliability (MTBF)	>> 100,000 hours (calculated using Bellcore Issue 6 TR-332, Case 2, Part I at 40°C)
Certifications	FCC Class B, CE, MIC, RoHS
TERMINAL SERVICES SOFTWARE	
Supported Operating Systems	Microsoft: Windows XP Professional, Windows 2000 Professional and Windows Server 2003 R2 SP2 Linux: several variants (refer to Support section of Website for latest supported versions of Linux)
Supported Software	PC applications including browsers, e-mail, office suites, media players, educational software and more Does not support 3D games or full screen home theater video applications.**
Maintenance	Online remote update via NComputing Management Console
SYSTEM REQUIREMENTS AND OPTIONS	
Host PC Configuration	See Recommended Host Configuration Guide at:*** http://www.ncomputing.com/ncomputing/products/technology.php
Kit Contents	One X300 Kit includes three (3) access terminals, one PCI card, terminal services software installation CD with user's guide, Quick Install Guide and low profile PCI bracket. Host PC, PS/2 keyboard, PS/2 mouse, speakers and other peripherals are NOT included and must be purchased separately.
Optional Software	NControl (remote control and management), NShield (Hard Drive partition recovery)

* Does not support USB to PS/2 adapters

** Application software and OS licenses for the host PC and access terminals may be required by the respective software vendor and must be purchased separately.

*** The number of users an individual host will support depends upon the host system capabilities as well as the applications used and performance expectations for those applications. It is recommended that new customers test their application(s) before adding additional users.

© Copyright 2007. NComputing, Inc. All rights reserved. Specifications are subject to change without notice. NComputing is trademark of NComputing Inc. Microsoft and Windows are registered trademarks of Microsoft Corporation. Intel and Pentium are registered trademarks of Intel Corporation. Linux is a registered trademark of Linus Torvalds. Other trademarks and trade names are the property of their respective owners.

11.12.07